

AMENDMENTS TO CLAIMS

Please amend claims 1, 4, 5 and 6 wherein underlining indicates additions and strikethrough indicates deletions, as follows:

1. (Currently Amended) A fastening assembly for securing a bed liner to a truck bed, the truck bed having an inward extended bed rail, the bed liner having at least one hole (42), the fastening assembly comprising:

a base member (1) for engaging a clamp member (4) through the bed liner hole (42), the base member (1) including a back surface that is pressed by the clamp member (4) with the bed liner wall and the bed rail in between, the base member having at least one extended direction control rod (14) extending generally perpendicularly from the back surface for insertion through the bed liner hole (42);

the clamp member (4) having at least one through hole (29) for insertion of the extended direction control rod (14) of the base member (1) therein, the hole (29) of the clamp member (4) can be moved along the extended direction control rod (14) of the base member (1) when the clamp member (4) is assembled to the base member (1), the hole extending through the clamp member from a first side to a second side, the first side facing the base member and the second side facing away from the base member in an assembled position, the clamp member able to be inserted through the hole (42) in the bed liner wall when the clamp member (4) is engaged with the base member (1); and

a tie-down ring for attaching to the base member (1).

2. (Original) The fastening assembly of claim 1 further comprising:
a screw (9) for securing the base member (1) to the clamp member (4).
3. (Previously Presented) The fastening assembly of claim 2 further comprising:
a ring (6) installed in an end of an internal threaded hole (31) of the clamp member (4).
4. (Currently Amended) The fastening assembly of claim 1 further comprising:
an elastic pad (2) which shall be placed between the back surface and the bed liner wall in ~~[[an]]~~the assembled position.

5. (Currently Amended) The fastening assembly of claim 1 further comprising:
a pad (5) for attaching to the clamp member (4), the pad (5) being constructed of rubber, the pad (5) shall be placed between the clamp member (4) and the inner surface of the bed rail in ~~[[an]]~~the assembled position.
6. (Currently Amended) The fastening assembly of claim 1 further comprising:
a supporting plate (7) for attaching to the inner surface of the bed rail, the supporting plate (7) shall be placed between the clamp member (4) and the inner surface of the bed rail in ~~[[an]]~~the assembled position.
7. (Original) The fastening assembly of claim 6 further comprising:
a double-sided adhesive tape (8) for attaching the supporting plate (7) to the inner surface of the bed rail.
8. (Original) The fastening assembly of claim 6 further comprising:
spring clips for securing the supporting plate (7) to the inner surface of the bed rail.
9. (Original) The fastening assembly of claim 1 wherein the base member (1) includes a force absorbing rod (16) extending therefrom to support the lower edge of the clamp member (4).
10. (Original) The fastening assembly of claim 1 wherein the direction control rod (14) has a contact plate (13) extending from both sides.